

**Test Report** No.: SDHL2004004099FT-01 Date: May 19, 2020 Page 1 of 3

GUANGDONG DONGTAI HARDWARE PRECISION MANUFACTURING CO., LTD INDUSTRY ROAD, LELIU PORT, LELIU, SHUNDE, FOSHAN, GUANGDONG, CHINA

The following sample(s) was / were submitted and identified on behalf of the client as:

Sample Description : HT SERIES DOUBLE-WALL DRAWER SYSTEM (MAGIC-PRO)

Style / Item No. : HT115004A11

Manufacturer : GUANGDONG DONGTAI HARDWARE PRECISION MANUFACTURING

CO., LTD

Country of Origin : CHINA

Sample Receiving Date : Apr.09, 2020

Test Performing Date : Apr.13, 2020 to May 06, 2020

# **Test Result Summary**

Test(s) Requested	Result(s)
Slide durability test with reference to clause 6.3.8 of EN 15338:2007+A1:2010	PASS
Summary:	

1. For further details, please refer to the following page(s).

Signed for and on behalf of Shunde Branch SGS-CSTC Co., Ltd.

Bill Wang

Approved signatory







Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="http://www.sgs.com/en/Terms-and-Conditions.aspx">http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx">http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention:To check the authenticity of testing / inspection report & certificate, please contact us at telephone:(86-755) 8307 1443, or email: CN.Doccheck@gs.com

| Fi,f<sup>®</sup>Buiding,European Industrial Partl,No.1 Shurthe South Road,|Nusha Sextion,Dallarg Tome,Shurthe Fostan,Garaptong,China 528333 t (86-757)22805888 f (86-757)22805888 www.sgs.group.com.cn 中国・广东・佛山市順徳区大良街道亦事处五沙順和南路「号欧洲工业园一号厂房首层 邮编: 528333 t (86-757)22805888 f (86-757)22805888 e sgs.china@sgs.com



**Test Report** No.: SDHL2004004099FT-01 Date: May 19, 2020 Page 2 of 3

### **TESTS AND RESULTS**

#### **Test Conducted:**

Slide durability test with reference to clause 6.3.8 of EN 15338:2007+A1:2010.

### No. of Sample:

1 set. For more sample information and pictures, please refer to the following page.

Test and Requirements	Test Results
6.3.8 Durability test  Open and close the extension element gently and without supporting the front for 100,000 cycles specified by applicant.  Open from the fully closed position to the point at which one-third of the inside length (depth) of the extension element, or at least 100 mm, remains inside the test frame. For extension elements, which are equipped with any sort of built-in stop in the open position, fully open the extension element without forcing the stop. If the extension element has a damper and/or a catch device, including a self opening or a self closing mechanism, this shall be allowed to operate at each cycle. Open and close the extension element via the force application point at a rate of 4 to 15 cycles per minute. The extension element shall fulfil its function and When the loading capacity is less than 40 kg, the opening and closing forces determined shall not exceed 50 N, When the loading capacity is not less than 40 kg, the opening and closing forces determined shall not exceed 12,5 % of the loading capacity.	PASS

#### Remark:

- 1. The total load 40 kg and cyclic number of 100,000 cycles are specified by applicant;
- 2. The dimension of testing drawer is 555 mm (W) x 515 mm (D) x 88 mm (H);
- 3. This test report is to supersede No. SDHL2004004099FT test report which was issued on May 06, 2020. And the original test reports (paper and electronic) are invalid;
- 4. For the sample information and pictures, please refer to the following page.



| 作。| 「Building European Industrial Part, Na.1 Sturine South Read, Wistra Sextion, Dallaring Town, Shunde, Frishard, Guargdong, China 528333 t (86-757)22805888 f (86-757)22805888 www.sgs.group.com.cn 中国・广东・佛山市原徳区大良街道办事处五沙厩和南路1号欧洲工业园一号厂房首层 邮编: 528333 t (86-757)22805888 f (86-757)22805888 e sgs.china@sgs.com



**Test Report** No.: SDHL2004004099FT-01 Date: May 19, 2020 Page 3 of 3

## **SAMPLE INFORMATION AND PICTURES**

Weight: 1067.8 g / piece


Length: 500 mm

Other Dimensions: /

## Sample as Received









\*\*\*End of Report\*\*\*



1F, if Building, European Industrial Park, Mo. 1. Stumbe South Road, Wilsaha Sedon, Dalang Town, Stunde, Fishan, Guangdong, China 528333 t (86—757) 22805888 f (86—757) 22805858 www.sgsgroup.com.cn 中国·广东·佛山市原德区大良街道办事处五沙颠和南路1号欧洲工业园一号厂房首层 邮编: 528333 t (86-757)22805888 f (86-757)22805858 e sgs.china@sgs.com